





SINGLE ACTING FULLY COMPENSATED COUNTERBALANCE VALVE - A1/B1 FLANGED 40x40

- Flow.....180 l/min
- Max working pressure.....410 bar
- Compensation.....Fully Compensated
- Weight G 1/2".....2,9 Kg
- Weight G 3/4".....3,3 Kg
- Tamper proof cap.....cod. 9021030190

SCHEME 40 - 80



SCHEME 42 - 82



Note:
- Pressure setting must be 30% higher than pressure induced by the load.
- To be used only with A/B closed center spools.

	a	b	c	d	e	f
04	70	39,5	142	83	10,5	40
05	80	39,5	147	86	10,5	43

Ordering code
H 1 5 0 6 C S 0 0

PILOT RATIO	
40	4:1
42	4:1 ADJUSTABLE DUMP SCREW
80	8:1
82	8:1 ADJUSTABLE DUMP SCREW

SPRINGS	4:1		8:1
	2	4	4
Setting range min.-max. [bar]	80 - 210	80 - 410	140 - 410
Pressure Increase [bar/turn]	40	72	72
Standard setting 4 l/min [bar]	200	350	350

PORTS	04	05
A,B	G 1/2"	G 3/4"
M	G 1/4"	G 1/4"
A1,A2	Ø 12	Ø 12

