









Technical Data	U.S. Units	Metric Units
Cavity	T-2A	
Body Features	Cushion lock with make up checks and shuttle	
Body Type	Line mount	
Interface	None	
Open Cavity Quantity	2	
Weight	7.355 lb.	3,336 kg.
Mounting Hole Diameter	.41 in.	10,4 mm
Mounting Hole Depth	Through	
Mounting Hole Quantity	2	
Includes integral cartridge(s)	Yes (see Included Components)	



Notes

- Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
- This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.

Port Headings		
Product	Port	Size
5BK	Ports C1,C2,V1,V2	SAE 10
5BK	Port S	SAE 4
5BK	Port T	SAE 12



3	CSAD-XXN			SHUTTLE VALVE	1
2	CXFA-XAN			CHECK VALVE	4
1	153-442-003		6061-T6 ALUMINUM	BODY	1
I T E M	PART NO.	SETTING	MATERIAL	PART NAME	Q T Y
MODEL 5BK			ALL DIMENSIONS IN INCH VIEWS ARE THIRD ANGLE		
DESCRIPTION T-2A Line mount (See Technical Data for Body Features)			DATE Feb-10-26	SCALE 0.791	DWG SIZE C SHEET 1
			<div> <div>FIRST ANGLE</div> <div>THIRD ANGLE</div> </div> <div>SUN hydraulics®</div>		