










Notes

- Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
- This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.
- Body Features: Ninety degree with reverse flow check, accepts standard and weatherized coils.

Port Headings		
Product	Port	Size
A7U	Ports 1 & 2	3/8" BSPP
A7U	Port 3	1/4" BSPP
A7U	Gage Port	1/4" BSPP

Technical Data	U.S. Units	Metric Units
Cavity	T-11A	
Body Features	(See Notes)	
Body Type	Line mount	
Interface	None	
Open Cavity Quantity	1	
Weight	2.006 lb.	0,910 kg.
Mounting Hole Diameter	.34 in.	8.6 mm
Mounting Hole Depth	Through	
Mounting Hole Quantity	2	
Includes integral cartridge(s)	Yes (see Included Components)	



2	CXCD-XCN			CHECK VALVE	1		
1	174-485-008		6061-T6 ALUMINUM	BODY	1		
ITEM	PART NO.	SETTING	MATERIAL	PART NAME	QTY		
MODEL A7U			ALL DIMENSIONS IN INCH VIEWS ARE THIRD ANGLE		FIRST ANGLE  THIRD ANGLE 		
DESCRIPTION T-11A Line mount (See Notes for Body Features)			DATE Feb-05-25	SCALE 1.182	DWG SIZE C	SHEET 1	

