










Notes

1. Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
2. This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.

Port Headings		
Product	Port	Size
B3K	Ports 1 & 2	SAE 10
B3K	Port 3	SAE 6
B3K	Gage Port	1/4" NPTF

Technical Data	U.S. Units	Metric Units
Cavity	T-2A	
Body Features	Through port 2 with reverse flow check	
Body Type	Line mount	
Interface	None	
Open Cavity Quantity	1	
Weight	3.420 lb.	1,551 kg.
Mounting Hole Thread	.375-16 UNC - 2B in.	
Mounting Hole Depth	.62 in.	15,7 mm
Mounting Hole Quantity	2	
Includes integral cartridge(s)	Yes (see Included Components)	

2	CXED-XCN			CHECK VALVE	1	
1	151-158-005		6061-T6 ALUMINUM	BODY	1	
ITEM	PART NO.	SETTING	MATERIAL	PART NAME	QTY	
MODEL			ALL DIMENSIONS IN INCH VIEWS ARE THIRD ANGLE			
B3K			FIRST ANGLE 		THIRD ANGLE 	
DESCRIPTION			DATE	SCALE	DWG SIZE	SHEET
T-2A Line mount Through port 2 with reverse flow check			Jul-23-26	0.914	C	1
						