MODEL
COKA

Pilot-to-close check valve
SERIES 4 / CAPACITY: 240 gpm / CAVITY: T-19AU

sunhydraulics.com/model/COKA





CONFIGURATION

X	Control	Not Adjustable
A	Cracking Pressure	4 psi (0,3 bar)
N	Seal Material	Buna-N
(none)	Material/Coating	

This valve is a spring biased closed, pilot-to-close check cartridge that has a 1.8:1 pilot ratio. The valve allows flow from port 1 to port 2 and blocks reverse flow. Pressure at the pilot port opposes pressure at port 1 at a ratio of 1.8:1. This valve is most often used in regeneration circuits.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-19AU
Series	4
Capacity	240 gpm
Maximum Operating Pressure	5000 psi
Pilot Ratio	1.8:1
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.
Valve Hex Size	1 5/8 in.
Valve Installation Torque	350 - 375 lbf ft
Seal kit - Cartridge	Buna: 990019007
Seal kit - Cartridge	Polyurethane: 990019002
Seal kit - Cartridge	Viton: 990019006
Model Weight	2.50 lb.

CONFIGURATION OPTIONS

Model Code Example: COKAArray

CONTROL (X)	CRACKING PRESSURE (A)	SEAL MATERIAL (N)	MATERIAL/COATING
X Not Adjustable	**A** 4 psi (0,3 bar)	**N** Buna-N	Standard Material/Coating
	B 15 psi (1 bar)	**V** Viton	**/LH** Mild Steel, Zinc-Nickel
	C 30 psi (2 bar)		
	D 50 psi (3,5 bar)		
	E 75 psi (5 bar)		
	F 100 psi (7 bar)		

© 2026 Sun Hydraulics

TECHNICAL FEATURES

- These valves will work in Sun's standard T-19A cavity at lower capacity. To realize the full stated capacity, the T-19AU cavity should be used.
- Nominal pilot ratio is 1.8:1. This means that a pressure of 1000 psi (70 bar) at the pilot port will close a valve against a pressure of 1800 psi (125 bar) at port 1. Any decay or loss of pilot pressure could allow the valve to open, even if it is a momentary decay or loss.
- Pressure at the port 2 area directly opposes pilot pressure.
- Reverse flow through the valve from port 2 to port 1 is not possible under any condition.
- With equal pressures at all ports the valve is closed.
- Corrosion resistant cartridge valves are intended for use in corrosive environments and are identified by the model code suffix /AP or /LH (see CONFIGURATION section). For further details, please see the Materials of Construction page under TECHNICAL RESOURCES.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES





© 2026 Sun Hydraulics