


CONFIGURATION

E Control	External 4-SAE Drain Port
H Minimum Pilot Pressure	300 psi (20 bar)
N Seal Material	Buna-N



This is a normally closed, balanced poppet, switching element. When the external vent port is blocked, the poppet remains in the closed position. Venting the external port shifts it to the open position, provided there is sufficient pressure at port 3.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-17A
Series	3
Capacity	60 gpm
Maximum Operating Pressure	5000 psi
Minimum Pilot Pressure Required to Shift Valve	300 psi
Control Pilot Flow	See Performance Data
Maximum Valve Leakage at 110 SUS (24 cSt)	10 drops/min.@5000 psi
Pilot Volume Displacement	.05 in ³
Valve Hex Size	1 1/4 in.
Valve Installation Torque	150 - 160 lbf ft
Seal kit - Cartridge	Buna: 990017007
Seal kit - Cartridge	Polyurethane: 990017002
Seal kit - Cartridge	Viton: 990017006
Model Weight	1.33 lb.

CONFIGURATION OPTIONS

Model Code Example: DKHDArray

CONTROL	(E)	MINIMUM PILOT PRESSURE	(H)	SEAL MATERIAL	(N)
E External 4-SAE Drain Port		H 300 psi (20 bar)		N Buna-N	
				V Viton	

TECHNICAL FEATURES

- Unique balanced construction provides predictable switching with 5000 psi (350 bar) at port 1 and port 2, with the external drain port open and a minimum pilot pressure of 300 psi (20 bar).
- The external -4 SAE vent port may be directly connected to a pilot switching valve. The pilot valve should have a leakage rate of less than 10 drops/min (0,7 cc/min). and be able to satisfy the pilot flow requirements. Sun model DAA*-*** solenoid pilot valve is ideal for this application.
- These valves are hydraulically balanced between port 1 and port 2.
- Leakage rate between port 1 and port 2 is very low, typically less than 10 drops/min. at 5000 psi (0,7 cc/min at 350 bar).
- Port 1 and port 2 are fully sealed from port 3.
- All ports will accept 5000 psi (350 bar).
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

