


Z-Control, C-Poppet



This solenoid-operated 2-way, 2-position cartridge is a direct-acting, poppet-style directional valve. Due to the poppet-style construction, this valve has extremely low leakage.

Many poppet style directional valves pass a small amount of fluid when the pressure across them changes suddenly. This is due to the compressibility of the fluid. This valve has been designed to prevent this from happening.

The position switch provides confirmation that the valve is in the non-energized position. [Click Here for the position sensor pin diagram](#)

CONFIGURATION

C Spool Configuration	Normally Closed
N Seal Material	Buna-N
224 Coil	DIN 43650-Form A, 24 VDC

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-13A
Series	1
Capacity	6 gpm
Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	10 drops/min. @5000 psi
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
Solenoid Tube Diameter	.75 in.
Valve Hex Size	7/8 in.
Valve Installation Torque	30 - 35 lbf ft
Seal kit - Cartridge	Buna: 990413007
Seal kit - Cartridge	EPDM: 990413014
Seal kit - Cartridge	Polyurethane: 990413002
Seal kit - Cartridge	Viton: 990413006
Model Weight	2.09 lb.

SWITCH SPECIFICATIONS

Supply Voltage	20-30 VDC
Operating Temperature Range	-25 to 80 °C
Vibration	≥ 50g, 0-500 impulses/sec
Shock	>50 g, 1ms
Reverse Polarity Protection	Yes
Maximum Output Load	≤ 400 mA, Duty Ratio 100%
Short Circuit Protection	Yes, Load Short Unlimited
Turn On Time	≤ 25 ms
Hysteresis	≤ .002 in.
Thermal Shift - 0 to 80 °C ≤ ±	.004 in.
EMC	DIN EN 61000-6-1/2/3/4
Connector	M12 X 1 (4) Pin
Connector Environment Rating	IP65

NOTES

An additional 2.00 inches (50,8 mm) beyond the valve extension is needed for coil installation and removal.

CONFIGURATION OPTIONS


Model Code Example: DTCAZCN224

SPOOL CONFIGURATION	(C)	SEAL MATERIAL	(N)	COIL *	(224)
C Normally Closed		N Buna-N		224 DIN 43650-Form A, 24 VDC	
H Normally Open		E EPDM		212 DIN 43650-Form A, 12 VDC	
		V Viton		912 Deutsch DT04-2P, 12 VDC	
				924 Deutsch DT04-2P, 24 VDC	
* Additional coil options are available					

TECHNICAL FEATURES

- A coil must be ordered with this cartridge. This cartridge is supplied as a sealed, factory set unit and is not field serviceable. If the assembly requires changes or service it needs to be returned to the factory. Any tampering will violate the product warranty.
- Position switch is CE approved.
- When torquing this cartridge into its cavity, a crow's foot wrench or similar will be required since the position switch precludes the use of a deep socket wrench.
- The solenoid tube assembly is fatigue rated for 5000 psi (350 bar) service.
- This valve is direct actuated and requires no minimum hydraulic pressure for operation.
- This valve is suitable for load holding applications. In the event of power failure, the valve will spring closed.
- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.
- This valve utilizes a wet armature design. This means that the working fluid surrounds the armature and is exposed to the heat generated by the coil. This can be a factor if the coil is energized for long periods of time. Some fluids, notably water/glycol mixtures, break down at these temperatures over time and form varnishes that will affect the function of the cartridge.
- The solenoid's unique magnetic design results in a high efficiency solenoid, yielding high spool actuating force per Watt expended, leading to reliable valve shifting.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES



RELATED MODELS

- [DTCA](#) 2-way, direct-acting, solenoid-operated directional blocking poppet valve with overlap
- [DTCAS](#) 2-way, direct-acting, soft shift, solenoid-operated directional blocking poppet valve with overlap