





CONFIGURATION

X	Control	Not Adjustable
A	Setting Range	Replaceable Orifice .2 - 25 gpm (0.8 - 95 L/min.)
N	Seal Material	Buna-N
(none) Material/Coating		

Fixed-orifice, pressure-compensated flow controls with reverse-flow check provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. An integral high-capacity check valve provides unrestricted flow from port 2 to port 1. The flow setting is specified by the user and is set at the factory.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-16A
Series	3
Capacity	25 gpm
Maximum Operating Pressure	5000 psi
Valve Hex Size	1 1/4 in.
Valve Installation Torque	150 - 160 lbf ft
Adjustment Screw Internal Hex Size	5/32 in.
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990016007
Seal kit - Cartridge	Polyurethane: 990016002
Seal kit - Cartridge	Viton: 990016006
Model Weight	0.95 lb.

CONFIGURATION OPTIONS

Model Code Example: FCEBXAN

CONTROL	(X) SETTING RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	A Replaceable Orifice .2 - 25 gpm (0.8 - 95 L/min.)	N Buna-N	Standard Material/Coating
L Tuning Adjustment		V Viton	/AP Stainless Steel, Passivated
C Tamper Resistant - Factory Set			/LH Mild Steel, Zinc-Nickel
K Handknob			

TECHNICAL FEATURES

- Customer must specify a flow rating. Factory set flow ratings are within +/- 10% of the requested setting.
- All 2-port flow control cartridges are physically and functionally interchangeable (i.e. same flow path, same cavity for a given frame size). However, cartridge extension dimensions from the mounting surface may vary.
- The tuneable control option provides +/- 22% variation from the nominal factory pre-set flow. Turn the adjustment clockwise to increase.
- The sharp-edged orifice design minimizes flow variations due to viscosity changes.
- Corrosion resistant cartridge valves are intended for use in corrosive environments and are identified by the model code suffix /AP for external stainless steel components, or /LH for external zinc-nickel plated components. See the CONFIGURATION section for all options. For further details, please see the Materials of Construction page located under TECH RESOURCES.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

