

CONFIGURATION

X	Control	No Manual Override
C	Flow Rate	.1 - 6 gpm (0,4 - 23 L/min.)
N	Seal Material	Buna-N
(none)	Coil	No coil

This valve is a 3-way, meter-in, electro-proportional throttle. The flow path, unenergized, has the supply blocked at port 1 and port 2 connected to tank at port 3. Energizing the coil generates a closing force on the spool, creating a metering orifice in the 1 to 2 direction that is proportional to the coil command current. The valve self-compensates in the 1 to 2 direction and with the addition of an external compensator will provide pressure compensated flow control. Flow in the 2 to 3 direction is not proportional.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-11A
Series	1
Capacity	6 gpm
Maximum Valve Leakage at 110 SUS (24 cSt)	2 in ³ /min.@1000 psi
Manual Override Force Requirement	5 lbs/1000 psi @ Port 1
Manual Override Stroke	.10 in.
Solenoid Tube Diameter	.63 in.
Valve Hex Size	7/8 in.
Valve Installation Torque	30 - 35 lbf ft
Seal kit - Cartridge	Buna: 990411007
Seal kit - Cartridge	Viton: 990411006
Seal and nut kit - Coil	Viton: 990740006
Model Weight	0.78 lb.

PROPORTIONAL PERFORMANCE DATA

Hysteresis (with dither)	<4%
Hysteresis with DC input	<8%
Linearity (with dither)	<2%
Repeatability (with dither)	<2%
Recommended dither frequency	140 Hz
Deadband, nominal (as a percentage of input)	60%

CONFIGURATION OPTIONS


Model Code Example: FMDGArray

CONTROL	(X) FLOW RATE	(C) SEAL MATERIAL	(N) COIL *
X No Manual Override	C .1 - 6 gpm (0,4 - 23 L/min.)	N Buna-N	No coil
D Twist/Lock (Dual) Manual Override	A .1 - 1.6 gpm (0,4 - 6.1 L/min.)	V Viton	* Additional coil options are available
L Twist/Lock (Detent) Manual Override	B .1 - 4 gpm (0,4 - 15 L/min.)		
M Manual Override			
T Twist (Momentary) Manual Override			

TECHNICAL FEATURES

- The transition between positions is closed.
- Using 2 3-ways to create a 4-way allows one to choose existing flow ranges instead of cutting a special spool.
- These valves may be pressure compensated by an external, modulating, logic element. Use LR_C-XHN for a bypass circuit or LP_C-XHN for a restrictive circuit.
- The valve provides a degree of self-compensation and may be used as a flow control. To increase the accuracy of flow control, an external, modulating, logic element can be used to maintain a constant flow over a wider range of flows and pressures. See performance curves for additional information.
- All ports will accept 5000 psi (350 bar).
- All configurations of this valve include zinc-nickel plating as standard for 1000-hour salt fog protection.
- This valve can be used with both the 740 Series high-power coils and 747 Series hazardous location coils.
- A wide variety of coil termination and voltage options are available, with and without surge protection. See the CONFIGURATION section.
- Coil connector options offer ratings up to IP69K. See individual coil product pages for details.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.


PERFORMANCE CURVES



FMDG-XA*


Flow vs. Coil Current (Flow 1 to 2)

Compensated with LPDC-XHN




FMDG-XA*

Typical Pressure Differential
vs. Flow



FMDG-XB*


Flow vs. Coil Current (Flow 1 to 2)



FMDG-XB*


Flow vs. Coil Current (Flow 1 to 2)

Compensated with LPDC-XHN




FMDG-XB*

Typical Pressure Differential vs. Flow



FMDG-XC*


Flow vs. Coil Current (Flow 1 to 2)



FMDG-XC*


Flow vs. Coil Current (Flow 1 to 2)

Compensated with LPDC-XHN



FMDG-XC*

Typical Pressure Differential vs. Flow



FMDG

Typical Pressure Differential vs. Flow (Port 2 to Port 3)

