






Technical Data	U.S. Units	Metric Units
Cavity	T-17A	
Body Features	Ninety degree with reverse flow check - reducing	
Body Type	Line mount	
Interface	None	
Open Cavity Quantity	1	
Weight	5.805 lb.	2,633 kg.
Mounting Hole Diameter	.41 in.	10,4 mm
Mounting Hole Depth	Through	
Mounting Hole Quantity	2	
Includes integral cartridge(s)	Yes (see Included Components)	












Notes

1. Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
2. This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.



Port Headings		
Product	Port	Size
H4N	Ports 1 & 2	SAE 20
H4N	Port 3	SAE 12
H4N	Gage Port	1/4" NPTF

ITEM	PART NO.	SETTING	MATERIAL	PART NAME	QTY
2	CXGDXCN			CHECK VALVE	1
1	150-754-006		6061-T6 ALUMINUM	BODY	1

MODEL: H4N

ALL DIMENSIONS IN INCH VIEWS ARE THIRD ANGLE

FIRST ANGLE / THIRD ANGLE

DESCRIPTION: T-17A Line mount (See Technical Data for Body Features)

DATE	SCALE	DWG SIZE	SHEET
Nov-26-24	0.799	C	1

sun hydraulics