










Notes

1. Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
2. This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.

Port Headings		
Product	Port	Size
HEL	Ports 1, 2, 3	SAE 12
HEL	Gage Port	1/4" NPTF

Technical Data	U.S. Units	Metric Units
Cavity	T-17A	
Body Features	Ninety degree with high capacity port 3 and gauge port	
Body Type	Line mount	
Interface	None	
Open Cavity Quantity	1	
Weight	2.902 lb.	1,316 kg.
Mounting Hole Diameter	.42 in.	10,7 mm
Mounting Hole Depth	Through	
Mounting Hole Quantity	2	

I	150-600-004		6061-T6 ALUMINUM	BODY	I
I T E M	PART NO.	SETTING	MATERIAL	PART NAME	Q T Y
MODEL			ALL DIMENSIONS IN INCH VIEWS ARE THIRD ANGLE		FIRST ANGLE THIRD ANGLE
DESCRIPTION			DATE	SCALE	
T-17A Line mount (See Technical Data for Body Features)			Oct-16-23	1:130	DWG SIZE C
					SHEET 1
					SUN hydraulics®