










Technical Data	U.S. Units	Metric Units
Cavity	T-17A	
Body Features	Cushion lock	
Body Type	Line mount	
Interface	None	
Open Cavity Quantity	2	
Weight	11.582 lb.	5,254 kg.
Mounting Hole Diameter	.53 in.	13,5 mm
Mounting Hole Depth	Through	
Mounting Hole Quantity	2	
Includes integral cartridge(s)	Yes (see Included Components)	



Notes

- Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
- This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.



Port Headings		
Product	Port	Size
HMX	Ports C1,C2,V1,V2	1" BSPP
HMX	Port T	1 1/4" BSPP

2	CXGDXCN			CHECK VALVE	2
1	151-179-005		6061-T6 ALUMINUM	BODY	1
ITEM	PART NO.	SETTING	MATERIAL	PART NAME	QTY
MODEL			ALL DIMENSIONS IN INCH VIEWS ARE THIRD ANGLE		
DESCRIPTION			DATE	SCALE	DWG SIZE SHEET
T-17A Line mount Cushion lock			Jun-19-26	0.657	C 1
			FIRST ANGLE THIRD ANGLE 		