









Notes

1. Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
2. This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.

Port Headings		
Product	Port	Size
IED	Ports 1 & 2	3/4" NPTF
IED	Gage Port	1/4" NPTF

Technical Data	U.S. Units	Metric Units
Cavity	T-16A	
Body Features	Through port with gauge port	
Body Type	Line mount	
Interface	None	
Open Cavity Quantity	1	
Weight	3.323 lb.	1,507 kg.
Mounting Hole Thread	.375-16 UNC - 2B in.	
Mounting Hole Depth	.62 in.	15,7 mm
Mounting Hole Quantity	2	

I	150-695-001		6061-T6 ALUMINUM	BODY	I
I T E M	PART NO.	SETTING	MATERIAL	PART NAME	Q T Y
MODEL IED			ALL DIMENSIONS IN INCH VIEWS ARE THIRD ANGLE		FIRST ANGLE THIRD ANGLE
DESCRIPTION T-16A Line mount Through port with gauge port			DATE Jun-12-25	SCALE 0.972	DWG SIZE C SHEET 1
SUN hydraulics®					