










Notes

1. Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
2. This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.

Port Headings		
Product	Port	Size
JKU	All Ports	3/8" BSPP

Technical Data		U.S. Units	Metric Units
Cavity		T-30A	
Body Features		Ninety degree	
Body Type		Line mount	
Interface		None	
Open Cavity Quantity		1	
Weight		0.837 lb.	0,380 kg.
Maximum Operating Pressure - 6061-T651 Aluminum		3000 psi	210 bar
Maximum Operating Pressure - 65-45-12 Ductile Iron		5000 psi	350 bar
Mounting Hole Diameter		.28 in.	7,1 mm
Mounting Hole Depth		Through	
Mounting Hole Quantity		2	

I	17G-198-006		6061-T6 ALUMINUM	BODY	
I T E M	PART NO.	SETTING	MATERIAL	PART NAME	
MODEL			ALL DIMENSIONS IN INCH VIEWS ARE THIRD ANGLE		FIRST ANGLE THIRD ANGLE
JKU					
DESCRIPTION			DATE	SCALE	DWG SIZE
T-30A Line mount Ninety degree			Aug-29-24	1.633	C
			SHEET	I	
					