






Technical Data	U.S. Units	Metric Units
Cavity	T-18A	
Body Features	Ninety degree with reverse flow check	
Body Type	Line mount	
Interface	None	
Open Cavity Quantity	1	
Weight	9.823 lb.	4,455 kg.
Mounting Hole Diameter	.41 in.	10,4 mm
Mounting Hole Depth	Through	
Mounting Hole Quantity	2	
Includes integral cartridge(s)	Yes (see Included Components)	












Notes

1. Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
2. This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.



Port Headings		
Product	Port	Size
LNN	Ports 1 & 2	SAE 20
LNN	Gage Port	1/4" NPTF

ITEM	PART NO.	SETTING	MATERIAL	PART NAME	QTY
2	CXJA-XAN			CHECK VALVE	1
1	151-922-006		6061-T6 ALUMINUM	BODY	1

MODEL					
LNN			ALL DIMENSIONS IN INCH VIEWS ARE THIRD ANGLE		FIRST ANGLE / THIRD ANGLE
DESCRIPTION	DATE	SCALE	DWG SIZE	SHEET	
T-18A Line mount Ninety degree with reverse flow check	Jun-05-25	0.726	C	1	SUN hydraulics®