





CONFIGURATION

A Control	External 1/4 NPTF Port
B Operating Range	50 - 1500 psi (3,5 - 105 bar)
N Seal Material	Buna-N

Air-controlled, pilot relief cartridges are used to remotely control the pressure setting of other pilot operated valves. Because capacity is limited to pilot flow, these valves should be used with valves with compatible pilot flows. They use compressed air over a diaphragm instead of an adjustable spring to control pressure setting, the air signal is supplied through a port in the hex-end of the cartridge.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-3A
Series	2
Capacity	.5 gpm
Maximum Operating Pressure	2000 psi
Pilot Ratio	20:1
Maximum Valve Leakage at 110 SUS (24 cSt)	5 drops/min.
Response Time - Typical	2 ms
Valve Hex Size	1 1/8 in.
Valve Installation Torque	45 - 50 lbf ft
Seal kit - Cartridge	Buna: 990203007
Seal kit - Cartridge	Viton: 990203006
Model Weight	0.54 lb.

CONFIGURATION OPTIONS

Model Code Example: RBABArray

CONTROL	(A) OPERATING RANGE	(B) SEAL MATERIAL	(N)
A External 1/4 NPTF Port	B 50 - 1500 psi (3,5 - 105 bar)	N Buna-N	V Viton

TECHNICAL FEATURES

- Maximum air pressure should not exceed 150 psi (10 bar).
- Pressure settings are insensitive to back pressure at the tank port (port 2). Back pressure should not exceed 1000 psi (70 bar).
- Capable of providing explosion proof remote control of the pressure setting, the hydraulic setting is directly proportional to the air setting at a ratio of 20:1 (hydraulic:air).
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

