






Notes

1. When using with SAE, dual seal cartridges, plug unused ports and expect higher pressure drops.
2. Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
3. This drawing is for reference only. It is generated by an automated process and does not fall under Sun's document control process.

Port Headings		
Product	Port	Size
U6D	Ports 2, 3, 4, 5	SAE 8
U6D	Ports 1 & 6	SAE 6



Technical Data	U.S. Units	Metric Units
Cavity	T-52A	
Body Features	Ninety degree	
Body Type	Line mount	
Open Cavity Quantity	1	
Weight	3.093 lb.	1,403 kg.
Mounting Hole Diameter	.34 in.	8.6 mm
Mounting Hole Depth	Through	
Mounting Hole Quantity	2	



I	172-791-004		6061-T6 ALUMINUM	BODY	
I T E M	PART NO.	SETTING	MATERIAL	PART NAME	Q T Y
MODEL			ALL DIMENSIONS IN INCH VIEWS ARE THIRD ANGLE		<div>FIRST ANGLE</div> <div>THIRD ANGLE</div>
U6D					
DESCRIPTION			DATE	SCALE	DWG SIZE
T-52A Line mount Ninety degree			Feb-09-26	0.891	C
			SHEET		
			I	<div>SUN hydraulics®</div>	